

- Product:** FS6
- Type:** 6ltr stored pressure AFFF extinguisher
- Application:** Hospitals, Supermarkets, Hotels, Restaurants, Paint shops, Clothing & Fabric industries, Industrial units, Offices etc.
- Features:** Slimline design (Ø 170mm diam.)
Easy to handle
Effective spray application
Ergonomic design
Replaces bulkier 9 lt. Water
Higher performance
- Benefits:** Uses 1% AFFF
Reduced service time
Reliability
Knockdown performance
Ideal for offices



Foam extinguishers are ideally suited where both class A & B fire risks exist. Aqueous film forming foam or aff is particularly suited to fight liquid spill fires such as petrol, oil, fats, paints etc. And works by forming a film on the liquid to extinguish the fire. This extinguisher has also passed the electrical conductivity test at 35kv.

TECHNICAL DATA

Model	Capacity	Type	Weight of charged extinguisher	Extinguishing agent	Volume of extinguishing agent	Working pressure	Discharge times	Range of jet horizontal	Temperature range	Height mm	Width mm	Depth mm
FS6	6 litre	Stored pressure	10.5 kg	1% AFFF	6 litre	7 bar	>36 sec.	4-6 m	-0°C to +60 °C	455	260	170

Antifyre (Ireland) Ltd.,
New Road,
Thomondgate,
Limerick

Tel: 061-455288
Fax: 061-326 756
www.antifyre.com